



## Features

- Fanless Design
- Flat Panel Design
- Total IP65
- Projected Capacitive Touch
- 11~32V DC Wide Range Power Input

## Specifications

### System

Processor	Intel Atom Processor N455 1.66GHz built-in
System Memory	1 x 204 Pin DDR3 800MHz SO-DIMM socket, default 2GB
System Chipset	Intel ICH8M
External I/O Port	2 x USB 2.0 connectors 1 x RJ-45 LAN connector 1 x DB-9 RS-232 (COM1) 1 x DB-9 RS-232/422/485 (COM3), default RS-485 1 x DC Power input 1 x power button with LED light
Storage	1 x 2.5" SATA HDD 1 x Internal CF Slot
Expansion Slots	None
Power Input	11~32V DC
Touch Screen	Projected Capacitive Touch
Light Transmission	90%
OS Support	Windows XP Professional, XP Embedded, Windows 7, Windows Embedded Standard 7

### LCD

Display Type	17" TFT-LCD
Max. Resolution	1280x1024
Max. Color	16.7M
Luminance (cd/m <sup>2</sup> )	350
View Angle	H:170° / V:160°
Backlight Lifetime	50,000 hrs

### Mechanical

Construction	Satinless steel
IP Rating	IP69K
Mounting	VESA 75x75 Mount
Dimension	432x358x65
Net Weight	8.8kgs

### Environmental

Operating Temperature	-20~50 °C
Storage Temperature	-30~70 °C
Storage Humidity	10~90% @40 °C non-condensing
Certificate	CE/FCC Class A

## Dimension

