

## HD 1080P FHD IR Bullet Camera    SF-FHD326PZ-4-ICR-S6



### Features:

- ◆ 1920\*1080 HD Video output
- ◆ 2.8~12 mm vari-focal lens, external adjustable
- ◆ 4 Array ir leds, 40m IR range, with IR CUT
- ◆ D-WDR, DNR, BLC, AGC, AWB
- ◆ Up-to 500m HD Transmission via Coaxial Cable
- ◆ Hybrid signal output: AHD/TVI/CVI/CVBS, 4 in 1
- ◆ Up: AHD, Down: CVI, Left: TVI, Right: CVBS
- Middle: OSD Menu

### Specification:

|                         |                                               |
|-------------------------|-----------------------------------------------|
| Model No.               | SF-AHD326PZ-ICR-S6                            |
| Image Sensor            | 1/2.8" SONY Exmor IMX323CMOS Sensor, 2.0MP    |
| DSP                     | FH8536                                        |
| Total Pixel             | 2.0MP, 1920H*1080V                            |
| Image System            | PAL/NTSC                                      |
| Min. Illumination       | 0.01Lux@F1.2, 0Lux (IR ON)                    |
| S/N Ratio               | ≥ 52dB                                        |
| Video Output            | AHD/TVI/CVI/CVBS Optional                     |
| Gamma Correction        | 0.45                                          |
| Day & Night             | Auto/ Color/ B/W/EXT                          |
| Shutter Speed           | 1/25s~1/45,000s                               |
| D-WDR                   | ON/OFF                                        |
| Digital Noise Reduction | 2D DNR                                        |
| White Balance           | ATW/MWB                                       |
| Exposure Mode           | Globe/Center/BLC/FLC                          |
| Defog                   | Auto/ON/OFF                                   |
| AGC                     | Auto/Manual                                   |
| Display Language        | Chinese, English, French, Russian, Italian    |
| Sharpness               | 1-20 Level Adjustable                         |
| Contrast                | 1-10 Level Adjustable                         |
| Color Gain              | 1-20 Level Adjustable                         |
| Voltage                 | DC12V±5 %                                     |
| Humidity                | ≤ 85%RH                                       |
| Operation Temp.         | -30℃~+50℃                                     |
| IR LED                  | 4pcs array ir leds , 40m IR range             |
| Lens Type               | 2.8~12mm vari-focal lens, external adjustable |
| Dimensions              | 260(L)*89(W)100(H)/mm                         |
| Weight                  | 0.8kg                                         |
| Package                 | 12pcs/CTN 528*345*470mm                       |