

ABOX-E70L

AI Edge vision computing Box PC

Intel 6th/7th/8th/9th Core i7/i5/i3 35W Desktop processors

Specification

V3.0

Key features:

- Support Intel® 6th/7th/8th/9th Core™ i7/i5/i3 desktop multicore processors;
- Q170 (Alternative C236) industrial chipset;
- 2 DDR4 SO-DIMM, Dual channels, MAX. UP TO 32GB;
- 3 Display ports, support 3 hard disks storage;
- Max. expansion up to 10 USB ports;
- Max. expansion up to 6 Intel RJ45 ports;
- Max. expansion up to 6 COM ports;
- Support wide voltage DC 9V ~ 36V power input.


Product Image



Technical Data

System	
CPU	Intel® 6 th /7 th /8 th /9 th Core™ i3/i5/i7 Desktop LGA1151 CPU, TDP=35W (fan-less)
Chipset	Intel® Q170 Chipset (Alternative C236 chipset)
Memory	2 x DDR4 SO-DIMM, 2133/2400 MHz, Dual channels, Max. single RAM up to 16GB, Max. up to 32GB
Storage	1 x 2.5" HDD, support 5~9.5mm, hot pluggable 1 x 2.5" HDD, support 5~9.5mm , Internal 1 x M.2 SATA 3.0 (22*42mm) , Internal
Display	1 x DP (Max. support resolution: 4096x2304 x24bpp, @ 60Hz) 1 x DVI-D (Max. support resolution: 1920x1200, @60Hz) 1 x VGA (Max. support resolution: 1920x1200, @60Hz)
Network	2 x Intel® Ethernet Connection; LAN1: I210/I211-AT, LAN2: I219-LM, support WOL
Wireless	1 x Mini-PCIE (Optional support 3G/4G/LTE, Wi-Fi/BT expansion)
Audio	1 x Mic-in + 1 x Audio-out
USB	6 x USB 3.0
COM	4 x DB9 RS232 (COM1/COM2 support RS485/RS422/RS232, BIOS controllable)
GPIO	8* GPIO, 1* 20 pins Phenix terminal (Optional)
Expansion	1* MXM expansion modules (support 4x GLAN) 1* aDoor expansion modules
Power	DC 9~36V input (1 x 4pin 5.08 phoenix terminal, with hole lock)
LED/Switch	1 x power button (including blue LED light)
Watchdog	Programmable 255 seconds
OS	6 th Core™: Windows 7/8.1/10 32 or 64 bits, Linux 7 th Core™: Windows 7/8.1/10 64 bits, Linux 8 th /9 th Core™: Windows 10 64 bits, Linux
RAID	0, 1
Structure	
Material	SGCC/Aluminum-alloy
Treatment	Hard anodizing treatment, scratch resistant
Color	Iron grey, industrial grey color
Cooling	Fan-less design
Weight	4.12kg (Net weight)
Dimension	268mm(L) x 194.2mm(W) x 67.7mm(H)
Mounting	Desktop, wall mount, VESA mount (100 x 100mm)
Environmental	
Operation temp.	Operating temp.: -20~60°C (Industrial SSD)
Storage temp.	Storage temp.: -40~80°C
Humidity	10%~90%@40°C (non-condensation)
Vibration	SSD : 3Grms@5~500Hz , random , 1 hr/axis ;
Shock	10G/peak (11ms sec)

Dimension & Interface



ABOX-E70L

Interface explanation

- | | | | | | |
|---------|------------|-----------|--------------------|---------|---------------|
| 1:DC IN | 2:LAN | 3:USB3.0 | 4:DVI-D | 5:Out | 6:COM |
| 7:Reset | 8:Power | 9:Earth | 10:Adoor/MXM Slots | 11:MIC | 12:VGA |
| 13:DP | 14:2.5"HDD | 15:USB3.0 | 16:SIM | 17:GPIO | Reserved hole |

Ordering Information

ABOX-E70L-xxxx	Intel LGA1151 xxxx 35W CPUs, 1*DVI-D, 1*DP, 1*VGA, 2*RJ45, 6*USB3.0, 4*RS232, Mic-In/Line-Out, DC 9~36V
Memory	DDR4 4G/8G/16G/32GB
Storage	SSD: 32GB/64GB/128GB/256GB/512GB/1TB HDD: 500GB/1TB
Wireless modules	Wifi: 802.11b/g/n Mini PCIe 150M 3G/4G: All network 4G module
MXM modules	
aDoor Modules	

Note: xxxx refer to CPU Code



The information in this specification is subject to change without notice.

All parts of Mainkco IPC documentation are protected by copyright law and all rights are reserved. This documentation may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form without prior consent, in writing, from TAICENN Technology.