

# APC-PC101LCQ-E5

10.1" widescreen Pcap. Touch Panel PC

## Specification

V2.0

### Key features:

- Intel Baytrail J1900 Quad-core processor;
- 10.1" TFT LCD, LED backlit, Resolution 1280 x 800;
- Multi-points 10 points Pcap. touch;
- Front panel IP65 rating, front 1 USB for RFID moduel;
- On-board 4GB DDR3 memory;
- Optional 1 standard aDoor module expansion, 1\* Mini-PCIe slot;
- 2 GLAN, 5 USB, 2 COM, 1 HDMI, 1 VGA, Mic-in/Line-out;
- Wide voltage input DC 12~28v.



### Product Image




## Technical Data

<b>System</b>	
BIOS	SPI AMI EEI BIOS
CPU	Intel Baytrail J1900 processor, Quad-core 2.0Ghz, burst to 2.42Ghz
Memory	On-board DDR3L 4GB RAM
Network	2* Intel I210AT (Optional 3G/4G/Wi-Fi)
Storage	1* 2.5"SATA + 1*mSATA
Audio	Realtek ACL 662 controller
Watch dog	Programmable 1~255 seconds
Operating System	Win7, Win8, Win 10, Linux, Unix
<b>I/O</b>	
Network	2x RJ45, 10/100/1000 Mbps
USB	3x USB 3.0 + 2x USB 2.0, 1x front USB
COM	2x DB9 RS232/RS485
Audio	Line-In, Line-Out
Display	1* HDMI + 1*VGA
Power Input	Coaxial power, 2.1mm, lockable
<b>LCD</b>	
Size/Type	10.1" WXGA TFT LCD
Resolution	1280* 800
Brightness	400 (cd/m <sup>2</sup> )
Brightness MTBF	WLED, 20 000 hours
Contrast ratio	800:1
Viewing angle	89/89/89/89 (Typ.)
<b>TOUCH</b>	
Type	Projective capacitive touch
Touch points	Multi points touch, max. up to 10 points
Durability	>100 000 000 times
Surface hardness	>Mohs 6H
Touch interface	USB
Response time	<5ms
<b>Structure</b>	
Front Panel	Magnesium-aluminum alloy, Anodizing treatment
Color	Light grey + Black
Mounting	Panel mounting, VESA100
Cut-out dimension	263.5 x 178 mm (W*H)
Product Dimension	272.1 x 192.7 x 63 mm (W*H*D)
Net weight	2.7 KG
<b>Power and Environmental</b>	
Voltage Input	DC 12~28V (Over-current, Over-voltage and reverse polarity protection)
Power Consumption	About 40 W
Working temperature	-20°C~+50 °C
Storage temperature	-30°C~+60 °C
Relative humidity	10~95%@10°C ( No condensation )
Vibration	50~500Hz, 1.5G, 0.15mm peak to peak
Shock	10G/peak ( 11ms sec )

**Dimension & Interface**



**APC-PC101LCQ-E5**



*Interface specification*

- |        |         |          |         |             |          |         |        |        |        |
|--------|---------|----------|---------|-------------|----------|---------|--------|--------|--------|
| 1:GND  | 2:DC IN | 3:USB    | 4:LAN   | 5:USB3.0    | 6:COM    | 7:COM   | 8:VGA  | 9:WIFI | 10:MIC |
| 11:USB | 12:SIM  | 13:aDoor | 14:WIFI | 15:Line Out | 16:Power | 17:HDMI | 18:USB | 19:LED |        |

**Mainkco IPC is a subsidiary brand of TAICENN Technology.**

*The information in this specification is subject to change without notice.*

*All parts of Mainkco IPC documentation are protected by copyright law and all rights are reserved. This documentation may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form without prior consent, in writing, from TAICENN Technology.*