


MPN: B-UTP620

CAT6 U/UTP Network Cable 20m, Grey

CAT6 cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 250Mhz (CAT6 standard) and are backwards compatible with CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space.



- Suitable for Gigabit (10/100/1000 Mbit) network
- CAT6 tested up to 250 MHZ
- with Latch Protection
- with slimline relief
- with gold-plated pins

Specifikationer

Features	AWG wire size	26/7
	Cable length	20 m
	Cable shielding	U/UTP (UTP)
	Cable standard	Cat6
	Cable type	Cat6
	Cabling technology	10/100/1000Base-T(X)
	Conductor material	Copper-Clad Aluminium (CCA)
	Conductor type	Stranded
	Connector 1	RJ45
	Connector 1 gender	Male
	Connector 2	RJ45
	Connector 2 gender	Male
	Data transfer rate	10000 Mbit/s
	Frequency	250 MHz
	Jacket material	Polyvinyl chloride (PVC)
	Product colour	Grey
RoHS compliance	Yes	
Other features	Product series	Round Cable
	Technical features	Kink Protection, strain relief and Latch Protection
Package dimensions (verified)	Depth Verified	15,8 cm
	Gross Weight Verified	0,532 kg
	Height Verified	6,9 cm
	Width Verified	16,3 cm
Packaging data	Quantity per pack	1 kusu
Product dimensions	Net Weight (Product, kg)	0,53 kg

Vendor information	Brand Name	MicroConnect
	Warranty	25 År
Weight & dimensions	Outer diameter	6 mm

Andre produkter i denne serie



Cable length	Black	Blue	Green	Grey
0.25 m	B-UTP60025S	B-UTP60025B	B-UTP60025G	B-UTP60025
0.5 m	B-UTP6005S	B-UTP6005B	B-UTP6005G	B-UTP6005
1.0 m	B-UTP601S	B-UTP601B	B-UTP601G	B-UTP601
1.5 m	B-UTP6015S	B-UTP6015B	B-UTP6015G	B-UTP6015
2.0 m	B-UTP602S	B-UTP602B	B-UTP602G	B-UTP602
3.0 m	B-UTP603S	B-UTP603B	B-UTP603G	B-UTP603
5.0 m	B-UTP605S	B-UTP605B	B-UTP605G	B-UTP605
7.5 m	B-UTP6075S	B-UTP6075B	B-UTP6075G	B-UTP6075
10.0 m	B-UTP610S	B-UTP610B	B-UTP610G	B-UTP610
15.0 m	B-UTP615S	B-UTP615B	B-UTP615G	B-UTP615
20.0 m	B-UTP620S	B-UTP620B	B-UTP620G	B-UTP620
25.0 m				B-UTP625
30.0 m				B-UTP630



Cable length	Orange	Purple	Red	White
0.25 m	B-UTP60025O	B-UTP60025P	B-UTP60025R	B-UTP60025W
0.5 m	B-UTP6005O	B-UTP6005P	B-UTP6005R	B-UTP6005W
1.0 m	B-UTP601O	B-UTP601P	B-UTP601R	B-UTP601W
1.5 m	B-UTP6015O	B-UTP6015P	B-UTP6015R	B-UTP6015W
2.0 m	B-UTP602O	B-UTP602P	B-UTP602R	B-UTP602W
3.0 m	B-UTP603O	B-UTP603P	B-UTP603R	B-UTP603W
5.0 m	B-UTP605O	B-UTP605P	B-UTP605R	B-UTP605W
7.5 m			B-UTP6075R	B-UTP6075W
10.0 m	B-UTP610O	B-UTP610P	B-UTP610R	B-UTP610W
15.0 m	B-UTP615O	B-UTP615P	B-UTP615R	B-UTP615W
20.0 m	B-UTP620O	B-UTP620P	B-UTP620R	B-UTP620W
25.0 m				
30.0 m				



Cable length	Yellow
0.25 m	B-UTP60025Y
0.5 m	B-UTP6005Y



Cable length	Yellow
1.0 m	B-UTP601Y
1.5 m	B-UTP6015Y
2.0 m	B-UTP602Y
3.0 m	B-UTP603Y
5.0 m	B-UTP605Y
7.5 m	B-UTP6075Y
10.0 m	B-UTP610Y
15.0 m	B-UTP615Y
20.0 m	B-UTP620Y
25.0 m	
30.0 m	