


MPN: B-UTP625

CAT6 U/UTP Network Cable 25m, Grey

CAT6 cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 250Mhz (CAT6 standard) and are backwards compatible with CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space.



- Suitable for Gigabit (10/100/1000 Mbit) network
- CAT6 tested up to 250 MHZ
- with Latch Protection
- with slimline relief
- with gold-plated pins

Specifikationer

Features	AWG wire size	24
	Cable length	25 m
	Cable shielding	U/UTP (UTP)
	Cable standard	Cat6
	Certification	EIA/TIA 568
	Conductor material	Copper-Clad Aluminium (CCA)
	Conductor type	Stranded
	Connector 1	RJ45
	Connector 1 gender	Male
	Connector 2	RJ45
	Connector 2 gender	Male
	Data transfer rate	10000 Mbit/s
	Frequency	250 MHz
	Jacket material	Polyvinyl chloride (PVC)
	Product colour	Grey
	RoHS compliance	Yes
Other features	Product series	Round Cable
	Technical features	Kink Protection, strain relief and Latch Protection
Package dimensions (verified)	Depth Verified	19,8 cm
	Gross Weight Verified	0,606 kg
	Height Verified	7,5 cm
	Width Verified	19,9 cm
Packaging data	Quantity per pack	1 kusû
Product dimensions	Net Weight (Product, kg)	0,506 kg
Vendor information	Brand Name	MicroConnect

Vendor information	Warranty	25 År
Weight & dimensions	Outer diameter	6 mm

Andre produkter i denne serie



Cable length	Black	Blue	Green	Grey
0.25 m	B-UTP60025S	B-UTP60025B	B-UTP60025G	B-UTP60025
0.5 m	B-UTP6005S	B-UTP6005B	B-UTP6005G	B-UTP6005
1.0 m	B-UTP601S	B-UTP601B	B-UTP601G	B-UTP601
1.5 m	B-UTP6015S	B-UTP6015B	B-UTP6015G	B-UTP6015
2.0 m	B-UTP602S	B-UTP602B	B-UTP602G	B-UTP602
3.0 m	B-UTP603S	B-UTP603B	B-UTP603G	B-UTP603
5.0 m	B-UTP605S	B-UTP605B	B-UTP605G	B-UTP605
7.5 m	B-UTP6075S	B-UTP6075B	B-UTP6075G	B-UTP6075
10.0 m	B-UTP610S	B-UTP610B	B-UTP610G	B-UTP610
15.0 m	B-UTP615S	B-UTP615B	B-UTP615G	B-UTP615
20.0 m	B-UTP620S	B-UTP620B	B-UTP620G	B-UTP620
25.0 m				B-UTP625
30.0 m				B-UTP630



Cable length	Orange	Purple	Red	White
0.25 m	B-UTP60025O	B-UTP60025P	B-UTP60025R	B-UTP60025W
0.5 m	B-UTP6005O	B-UTP6005P	B-UTP6005R	B-UTP6005W
1.0 m	B-UTP601O	B-UTP601P	B-UTP601R	B-UTP601W
1.5 m	B-UTP6015O	B-UTP6015P	B-UTP6015R	B-UTP6015W
2.0 m	B-UTP602O	B-UTP602P	B-UTP602R	B-UTP602W
3.0 m	B-UTP603O	B-UTP603P	B-UTP603R	B-UTP603W
5.0 m	B-UTP605O	B-UTP605P	B-UTP605R	B-UTP605W
7.5 m			B-UTP6075R	B-UTP6075W
10.0 m	B-UTP610O	B-UTP610P	B-UTP610R	B-UTP610W
15.0 m	B-UTP615O	B-UTP615P	B-UTP615R	B-UTP615W
20.0 m	B-UTP620O	B-UTP620P	B-UTP620R	B-UTP620W
25.0 m				
30.0 m				



Cable length	Yellow
0.25 m	B-UTP60025Y
0.5 m	B-UTP6005Y



Cable length	Yellow
1.0 m	B-UTP601Y
1.5 m	B-UTP6015Y
2.0 m	B-UTP602Y
3.0 m	B-UTP603Y
5.0 m	B-UTP605Y
7.5 m	B-UTP6075Y
10.0 m	B-UTP610Y
15.0 m	B-UTP615Y
20.0 m	B-UTP620Y
25.0 m	
30.0 m	