

313.1647P**CONNECTOR**

16A 3P+N+E 6h 346-415V 50Hz 60Hz
Perforating terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

CONNECTOR

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Perforating terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--