

592.R002-01

SP TWO WAY SWITCH
SP TWO WAY SWITCH 16AX NO+NC
1xM20 II 2GD



EN 60079-31 (2014)
EN 60079-1 (2014)
EN 60079-7 (2015)
EN IEC 60079-7/A1 (2018)
IEC 60079-1 (2014)
IEC 60079-0 (2017)
IEC 60079-7 (2017)
IEC 60079-31 (2022)
EN 60669-1 (2018)
IEC 60669-1 (2017)
EN IEC 60079-0 (2018)
EN IEC 60079-31 (2024)
ATEX directive 2014/34/EU

Commercial Series	ROCKER-EX[GD] Series
Synthetical description	SP TWO WAY SWITCH
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	16AX
Rated voltage	250V

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOPLASTIC
Protection degree IK	7J
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
GLOW WIRE	GW 960°C
Cable entry	1xM20
Cable size	ø10-14mm

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual
Instruction manual

■ OPTIONS & VARIOUS NOTES

Notes	NO+NC
Catalogue notes	Polyamide cable glands.
Catalogue notes	Cable glands also available in AISI 316L steel (on request).
Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.