

SWITCH DISCONNECTOR
20A 3/4P IP66 141x200x126mm II
2GD 7J EMERGENCY YELLOW/RED



ATEX directive 2014/34/EU

Commercial Series	ISOLATORS-EX[GD] Series
Synthetical description	SWITCH DISCONNECTOR
Type	EMERGENCY
Mounting version	SURFACE MOUNTING

Rated current	20A
Poles	3/4P
Rated insulation voltage (Ui)	690VAC
Current (Ie) in AC22A (690V)	20A
Current (Ie) in AC23A (500V)	20A
Current (Ie) in AC3 (500V)	20A
Terminals - Flexible wires	10mm ²
Terminals - Rigid wires	16mm ²

Group and categories EX II 2GD

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	STAINLESS STEEL [AISI316L]
Protection degree IP	IP66
Colour	YELLOW/RED
Cable entry	2xM25
Cable size	ø10-14mm
Protection degree IK	7J
Padlock	ø6mm
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Terminals tightening torque	0,8Nm

Dimensions 141x200x126mm

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)

Catalogue notes	Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
Catalogue notes	Earth-stud included
Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.