

SWITCH DISCONNECTOR
20A 3P IP65 105x150x82mm II 2D 7J
GENERAL GREY/BLACK



Commercial Series	ISOLATORS-EX Series
Synthetical description	SWITCH DISCONNECTOR
Type	GENERAL
Mounting version	SURFACE MOUNTING

Rated current	20A
Poles	3P

Group and categories EX	II 2D
Dust protection	Ex tb IIIC T90°C Db IP65

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	DIE-CAST ALUMINIUM
Protection degree IP	IP65
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
Protection degree IK	7J
Padlock	ø4,7mm
Ambient temperature Ta min	-25 °C
Ambient temperature Ta max	60 °C

Dimensions	105x150x82mm
------------	--------------

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)

Catalogue notes	Cable inlets 1xM20 (top): on request.
Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
Catalogue notes	Handle padlockable in OFF (3 padlocks) and ON (3 padlocks) position