

SWITCH DISCONNECTOR
20A 3P IP65 105x150x82mm II 2D
EMERGENCY YELLOW/RED



ATEX directive 2014/34/EU

Commercial Series	ISOLATORS-EX Series
Synthetical description	SWITCH DISCONNECTOR
Type	EMERGENCY
Mounting version	SURFACE MOUNTING

Rated current	20A
Poles	3P

Group and categories EX	II 2D
Dust protection	Ex tb IIIC T90°C Db IP65

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	DIE-CAST ALUMINIUM
Protection degree IP	IP65
Installation temperature	-25°C/+60°C
Colour	YELLOW/RED
Impact resistance	7J
Padlock	ø4,7mm
Ambient temperature Ta min	-25 °C
Ambient temperature Ta max	60 °C

Dimensions 105x150x82mm

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]
 Instruction manual
 Instruction manual

Catalogue notes	Cable inlets 1xM20 (top): on request.
	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
	Handle padlockable in OFF (3 padlocks) and ON (3 padlocks) position