

218.3237**PLUG****32A 3P+N+E 6h 346-415V 60Hz 50Hz****Screw terminals**

EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

EN 60309-1/A2 (2012)

EN 60309-2/A1 (2007)

EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Mounting version	PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--