

**672.4024.1102**

CONSUMER UNIT  
IP66 SURFACE MOUNTING M400 24  
MOD. 256x400x140mm GREY



EN 60670-1 (2005)  
EN 60670-24 (2013)  
EN 62208 (2011-10)

Low voltage direct. 2014/35/EU

### ■ GENERAL CHARACTERISTICS

|                         |                                |
|-------------------------|--------------------------------|
| Commercial Series       | DOMINO IP66 Series [enclosure] |
| Synthetical description | CONSUMER UNIT                  |
| Mounting version        | SURFACE MOUNTING               |

### ■ TECHNICAL CHARACTERISTICS

|                  |     |
|------------------|-----|
| Dissipable power | 30W |
|------------------|-----|

### ■ PHYSICAL CHARACTERISTICS

|                      |                  |
|----------------------|------------------|
| Colour               | GREY             |
| Material             | THERMOPLASTIC    |
| Mounting version     | SURFACE MOUNTING |
| Protection degree IP | IP66             |
| Protection degree IK | IK07             |

### ■ DIMENSIONAL CHARACTERISTICS

|             |               |
|-------------|---------------|
| Modularity  | M400          |
| N.° modules | 24 MOD.       |
| Dimensions  | 256x400x140mm |

### ■ DOWNLOAD

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)  
[Instruction manual](#)  
[Instruction manual](#)

### ■ OPTIONS & VARIOUS NOTES

|                 |  |
|-----------------|--|
| Catalogue notes | Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards   |
|                 | .1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm <sup>2</sup> - 5x16mm <sup>2</sup> ) |