

**805.RAS1620.EN**

**CABLE GLAND**  
**M20X1,5 EMC EPDM IP66/IP68 GREY**  
**II 2GD IM 2**



\* Product image may be indicative



IEC 62153-4-3 (2013)  
 IEC 62153-4-4 (2015)

ATEX directive 2014/34/EU  
 EMC directive 2014/30/EU

### ■ GENERAL CHARACTERISTICS

---

Commercial Series	UNION-EX[OTN] Series
Synthetical description	CABLE GLAND
Type	EMC

### ■ EX CHARACTERISTICS

---

Group and categories EX	II 2GD
	IM 2
Dust protection	Ex tb IIIC Db IP66

### ■ PHYSICAL CHARACTERISTICS

---

Protection degree IP	IP66/IP68
Gasket	EPDM
Material	NICKEL PLATED
Colour	GREY
Ambient temperature Ta min	-40 °C
Ambient temperature Ta max	100 °C

### ■ DIMENSIONAL CHARACTERISTICS

---

Thread (type)	Metric
Thread	M20X1,5
Cables (outer sheath)	ø4÷7mm
	ø7÷10mm
Wrench body fixing (C1)	24mm
Wrench nut fixing (C2)	24mm

### ■ DOWNLOAD

---

Technical drawing [PDF]  
 Technical drawing [DWG]  
 Technical drawing [STP]

### ■ OPTIONS & VARIOUS NOTES

---

Catalogue notes	EMC (Electromagnetic Compatibility) compliant connection
	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.