

805.RAS2520.EN**CABLE GLAND****M20X1,5 EMC EPDM IP66/IP68 GREY
II 2GD IM 2**

* Product image may be indicative

IEC 62153-4-3 (2013)
IEC 62153-4-4 (2015)ATEX directive 2014/34/EU
EMC directive 2014/30/EU**■ GENERAL CHARACTERISTICS**

Commercial Series	UNION-EX[OTN] Series
Synthetical description	CABLE GLAND
Type	EMC

■ EX CHARACTERISTICS

Group and categories EX	II 2GD IM 2
Dust protection	Ex tb IIIC Db IP66

■ PHYSICAL CHARACTERISTICS

Protection degree IP	IP66/IP68
Gasket	EPDM
Material	NICKEL PLATED
Colour	GREY
Ambient temperature Ta min	-40 °C
Ambient temperature Ta max	100 °C

■ DIMENSIONAL CHARACTERISTICS

Thread (type)	Metric
Thread	M20X1,5
Cables (outer sheath)	ø8÷10,5mm ø10,5÷13mm ø13÷15,5mm ø15,5÷18mm
Wrench body fixing (C1)	35mm
Wrench nut fixing (C2)	36mm

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	EMC (Electromagnetic Compatibility) compliant connection ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
-----------------	--