

**418.3267-7**

**FLUSH-MOUNTING SOCKET**  
**32A 6P+E 6h 380-415V 50Hz 60Hz**  
**75X75MM Screw terminals**



\* Product image may be indicative



EN 60309-1 (1999)  
 EN 60309-1/A1 (2007)  
 EN 60309-1/A2 (2012)

Low voltage direct. 2014/35/EU

## ■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-SEVEN Series
Synthetical description	FLUSH-MOUNTING SOCKET

### Description

The flush-mounting socket from the OPTIMA-SEVEN Series, engineered for robust electrical performance, is designed to handle a rated voltage of 380-415V and a rated current of 32A, making it suitable for demanding industrial environments. It features a 6P+E configuration with a 6h hour position, ensuring reliable connectivity. The socket operates efficiently at both 50Hz and 60Hz frequencies. With a high protection degree of IP66/IP67, it offers superior resistance to dust and water ingress. The screw terminals provide secure and stable connections, while the angled outlet design enhances accessibility and installation flexibility.

Mounting version	FLUSH MOUNTING
------------------	----------------

## ■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	6P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

## ■ PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)

## ■ DIMENSIONAL CHARACTERISTICS

Flange	75X75MM
--------	---------

## ■ DOWNLOAD

Technical drawing [PDF]  
 Technical drawing [DWG]  
 Technical drawing [STP]

## ■ OPTIONS & VARIOUS NOTES

Catalogue notes	Screw terminals
-----------------	-----------------