

759.3237-25

CORD EXTENSION
CORD EXTENSION 5x6mm² 25m



* Product image may be indicative



EN 60079-31 (2014)
 IEC 60079-0 (2017)
 EN 60079-7 (2015)
 IEC 60079-31 (2013)
 EN IEC 60079-7/A1 (2018)
 IEC 60079-7 (2017)
 EN 60079-1 (2014)
 EN IEC 60309-2:2022
 IEC 60079-31 (2022)
 EN IEC 60309-1:2022
 IEC 60309-4 (2012)
 EN IEC 60309-4 (2022)
 EN IEC 60079-0 (2018)
 IEC 60309-1 (2021)
 IEC 60309-2 (2021)

ATEX directive 2014/34/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-EX[GD] Series
Synthetical description	CORD EXTENSION

Description

The OPTIMA-EX[GD] Series - II 2GD cord extension is designed for rigorous industrial settings, delivering exceptional performance with a rated current of 32A and a rated voltage of 346-415V. Engineered with a protection degree of IP66, it offers outstanding resistance to dust and water ingress, ensuring reliability in challenging environments. The extension is equipped with a 25-meter cable length and a 5x6mm² cable section, providing extensive reach and dependable conductivity. This product is precisely crafted to adhere to stringent industrial standards, guaranteeing durability and efficiency in electrical distribution operations.

■ TECHNICAL CHARACTERISTICS

Poles	3P+N+E
Rated current	32A
Hour position	6h
Rated voltage	346-415V
Cable section	5x6mm ²

■ PHYSICAL CHARACTERISTICS

Protection degree IP	IP66
Material	ENGINEERING PLASTIC
Colour	BLACK

■ DIMENSIONAL CHARACTERISTICS

Cable length	25m
--------------	-----

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)
[Instruction manual](#)
[Instruction manual](#)
[Instruction manual](#)
[Instruction manual](#)