

SCM530B7S**FLUSH MOUNTING APPLIANCE
INLET****30A 4P 5W 7h 3ØY277/480V
120X120MM Screw terminals****UL 1682
CSA C22.2 No. 182.1 (1988)
UL 486E
CSA C22.2 No. 65-93****■ GENERAL CHARACTERISTICS**

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	The flush mounting appliance inlet from the EUREKA-HD[UL] Series is designed for a rated voltage of 3ØY277/480V and a current of 30A. Featuring 4P 5W poles and a 7h hour position, it is built to meet professional standards. The inlet offers a protection degree of IP44, ensuring reliable performance in various environments. It is equipped with screw terminals for secure connections. This UL listed product is compatible with 90° angled outlets, providing flexibility and efficiency in installation.
Mounting version	FLUSH MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	30A
Poles	4P 5W
Hour position	7h
Rated voltage	3ØY277/480V
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK10
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

■ DIMENSIONAL CHARACTERISTICS

Flange	120X120MM
--------	-----------

■ DOWNLOAD[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)**■ OPTIONS & VARIOUS NOTES**

Catalogue notes	UL listed
-----------------	-----------