

**644.0390**

**SURFACE MOUNTING BOX**  
**560x160x90mm IP66 GW 960°C**  
**COMPONENT BLACK**  
**THERMOSETTING**



\* Product image may be indicative



EN 60079-31 (2014)  
 IEC 60079-0 (2017)  
 IEC 60079-31 (2013)  
 EN 60079-7 (2015)  
 EN IEC 60079-7/A1 (2018)  
 IEC 60079-7 (2017)  
 IEC 60079-31 (2022)  
 EN IEC 60079-0 (2018)  
 ATEX directive 2014/34/EU

## ■ GENERAL CHARACTERISTICS

---

Commercial Series	ZENITH-P Series
Synthetical description	SURFACE MOUNTING BOX

## ■ EX CHARACTERISTICS

---

Group and categories EX	II 2GD
Modo protezione gas	Ex eb IIC Gb
Dust protection	Ex tb IIIC Db IP66

## ■ PHYSICAL CHARACTERISTICS

---

Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOSETTING
Impact resistance	7J
Equipment	Empty enclosure
GLOW WIRE	GW 960°C
Colour	BLACK
Ambient temperature Ta min	-60 °C
Ambient temperature Ta max	100 °C

## ■ DIMENSIONAL CHARACTERISTICS

---

Dimensions	560x160x90mm
------------	--------------

## ■ DOWNLOAD

---

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)  
[Instruction manual](#)  
[Instruction manual](#)  
[Instruction manual](#)

## ■ OPTIONS & VARIOUS NOTES

---

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
-----------------	--