

805.RN1620.EN

CABLE GLAND
M20X1,5 FOR UNARMORED CABLE
EPDM IP66/IP68 GREY II 2GD IM 2



* Product image may be indicative



IEC 61241-1 (2004-05)
 IEC 60079-7 (2006-07)
 IEC 60079-0 (2004-01)
 IEC 61241-0 (2004-07)
 IEC 60079-1 (2003-11)
 ATEX directive 2014/34/EU

■ GENERAL CHARACTERISTICS

Commercial Series	UNION-EX[OTN] Series
Synthetical description	CABLE GLAND
Type	FOR UNARMORED CABLE

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
	IM 2
Dust protection	Ex tb IIIC Db IP66

■ PHYSICAL CHARACTERISTICS

Protection degree IP	IP66/IP68
Gasket	EPDM
Material	NICKEL PLATED
Colour	GREY
Ambient temperature Ta min	-40 °C
Ambient temperature Ta max	100 °C

■ DIMENSIONAL CHARACTERISTICS

Thread (type)	Metric
Thread	M20X1,5
Cables (outer sheath)	ø4÷7mm
	ø7÷10mm
Wrench body fixing (C1)	24mm
Wrench nut fixing (C2)	24mm

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
	The cable gland kit is supplied with a set of rubbers for securing the cable; nut and gasket must be purchased separately.