

645.C6S010**CABINET**

300x300x210mm IP66 COMPONENT
GREY STAINLESS STEEL [AISI316L]
Silicone



* Product image may be indicative



EN 60079-31 (2014)

IEC 60079-0 (2017)

IEC 60079-31 (2013)

EN 60079-7 (2015)

IEC 60079-7 (2015)

IEC 60079-31 (2022)

EN IEC 60079-0 (2018)

ATEX directive 2014/34/EU

■ GENERAL CHARACTERISTICS

Commercial Series	ZENITH-S Series
Synthetical description	CABINET

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
Modo protezione gas	Ex eb IIC Gb
Dust protection	Ex tb IIIC Db IP66

■ PHYSICAL CHARACTERISTICS

Protection degree	Splash proof
Protection degree IP	IP66
Material	STAINLESS STEEL [AISI316L]
Impact resistance	7J
Gasket	Silicone
Colour	GREY
Ambient temperature Ta min	-50 °C
Ambient temperature Ta max	100 °C

■ DIMENSIONAL CHARACTERISTICS

Dimensions	300x300x210mm
------------	---------------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
	Standard version supplied without flange.
	For version with lock in AISI 316L add Y at the end of the code
	For version with lock in Zamak add Z at the end of the code
	Standard version supplied with double-bit lock.