

SCM560B7W

FLUSH MOUNTING APPLIANCE
INLET
60A 4P 5W 7h 3ØY277/480V
120X120MM Screw terminals



* Product image may be indicative



UL 1682
CSA C22.2 No. 182.1 (1988)
UL 486E
CSA C22.2 No. 65-93

GENERAL CHARACTERISTICS

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	
The EUREKA-HD[UL] Series flush mounting appliance inlet is engineered for high-performance electrical applications. It operates at a rated voltage of 3ØY277/480V and a rated current of 60A, ensuring efficient power distribution. Featuring a 4P 5W configuration with a 7h hour position, it is designed for demanding industrial environments. The inlet offers robust protection with an IP67 rating, providing excellent resistance against dust and water ingress. Equipped with screw terminals, it ensures secure and reliable connections. Available in a 90° angled outlet type, this UL listed product is a dependable choice for professionals seeking durable and efficient electrical solutions.	
Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	60A
Poles	4P 5W
Hour position	7h
Rated voltage	3ØY277/480V
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK10
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

DIMENSIONAL CHARACTERISTICS

Flange	120X120MM
--------	-----------

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	UL listed
-----------------	-----------