

SCM560C7W**CONNECTOR****60A 4P 5W 7h 3ØY277/480V Screw terminals**

* Product image may be indicative



UL 1682
CSA C22.2 No. 182.1 (1988)
UL 486E
CSA C22.2 No. 65-93
IEC 60309-1 (2021)
IEC 60309-2 (2021)

■ GENERAL CHARACTERISTICS

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	CONNECTOR

Description

The EUREKA-HD[UL] Series connector is engineered for robust electrical industrial applications, offering a rated voltage of 3ØY277/480V and a rated current of 60A. This connector features a 4P 5W configuration and a 7h hour position, ensuring reliable performance in demanding environments. With an IP67 protection degree, it provides superior resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is UL listed, guaranteeing compliance with stringent safety standards. This connector is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE
------------------	----------

■ TECHNICAL CHARACTERISTICS

Rated current	60A
Poles	4P 5W
Hour position	7h
Rated voltage	3ØY277/480V
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK10
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[STP\]](#)
[Technical drawing \[DWG\]](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	UL listed
-----------------	-----------