

561.32864**INTERLOCKED SOCKET**

32A 3P+E 3h 380V 50Hz / 440V 60Hz
60Hz 50Hz 106X240MM Screw
terminals With mechanical interlock



* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

EN IEC 60309-4 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	ADVANCE 2 Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	3h
Rated voltage	380V 50Hz / 440V 60Hz
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Contact material	CuZn (brass)
Cable entry	M25X1,5
Padlock	ø5mm

■ DIMENSIONAL CHARACTERISTICS

Flange	106X240MM
--------	-----------

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER
Catalogue notes	Cable gland included
	Open threaded cable entry
	Threaded cap/cable sleeve included